



Halogen non-reflector lamps – high-quality light and easy to use

Halogen non-reflector

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Benefits

- Optimal beam performance
- 100% Color Rendering Index (CRI)
- Constant light output throughout lifetime

Features

- Distortion-free, quartz bulb and precisely defined filament position
- Lamp replacement without adjustment
- XHP version with xenon gas for maximum light output
- Flat filament available

Halogen non-reflector

Application

- Studio, film, theatre and disco lighting
- Slide, overhead, profile and 8/16 mm film projectors
- Microscopes
- Optical equipment
- Slide and film viewers
- Surgery lamps
- Microfilm readers
- Dental lamps
- Spectrography

Versions



G5.3



GY6.35



G6.35



G4




G6.35 Axial



G4




Dimensional drawing



Product	D (max)	L (min)	L (max)	L	C	P (max)	P	P (min)
12345SL 20W	8,5 mm	19,25	19,75	19,5	30	0,75 mm	0,7	0,65
G4 12V		mm	mm	mm	mm		mm	mm
1CT/24								

Halogen non-reflector

Dimensional drawing



Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
6390 30W	8.5 mm	26.75	27.25	27	1.65	1.50	1.47	44 mm
G5.3 10.8V		mm	mm	mm	mm	mm	mm	
1CT/24								
14531 360W								
G5.3 82V 1CT								

Product
14623 95W G6.35 17V 1CT/10X10F
13701 110W G6.35 22.8V 1CT/10x10F
7158XHP 150W G6.35 24V 1CT/10X10F
7748XHP 250W G6.35 24V 1CT/10X10F
7724I 100W GY6.35 12V 1CT/10X10F
7724 100W GY6.35 12V 1CT/10X10F
6550 150W G6.35 15V 1CT/10X10F
7158 150W G6.35 24V 1CT/10X10F
7027 50W G6.35 12V 1CT/10X10F
7023 100W GY6.35 12V 1CT/10X10F

Product	D (max)	L (max)	C (max)
5761 30W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm
7388 20W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm
7387 10W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm
6605 10W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm

General Information

Main Application Projection

Mechanical and Housing

Bulb Material Quartz-UV Open

Operating and Electrical

Order Code	Full Product Name	Voltage (Nom)	Power (Rated) (Nom)
822234361803	6390 30W G5.3 10.8V 1CT/24	10.8 V	30 W
924041528894	14531 360W G5.3 82V 1CT	82 V	360 W
923870017103	7023 100W GY6.35 12V 1CT/10X10F	12 V	100 W
923872517103	7724 100W GY6.35 12V 1CT/10X10F	12 V	100 W

Order Code	Full Product Name	Voltage (Nom)	Power (Rated) (Nom)
923875717103	7724I 100W GY6.35 12V 1CT/10X10F	12 V	100 W
923870217103	7027 50W G6.35 12V 1CT/10X10F	12 V	50 W
923870520503	7158 150W G6.35 24V 1CT/10X10F	24 V	150 W
923870618503	6550 150W G6.35 15V 1CT/10X10F	15 V	150 W

Halogen non-reflector

Order Code	Full Product Name	Voltage (Nom)	Power (Rated)	
			(Nom)	(Nom)
924006520503	7748XHP 250W G6.35 24V 1CT/ 10X10F	24 V	250 W	
924031720503	7158XHP 150W G6.35 24V 1CT/ 10X10F	24 V	150 W	
924049819103	14623 95W G6.35 17V 1CT/10X10F	17 V	95 W	
923873910103	6605 10W G4 6V 1CT/10X10F	6 V	10 W	

Order Code	Full Product Name	Voltage (Nom)	Power (Rated)	
			(Nom)	(Nom)
923874510103	7387 10W G4 6V 1CT/10X10F	6 V	10 W	
923874610103	7388 20W G4 6V 1CT/10X10F	6 V	20 W	
923931110103	5761 30W G4 6V 1CT/10X10F	6 V	30 W	
924031928303	13701 110W G6.35 22.8V 1CT/10x10F	22.8 V	110 W	
924068417104	12345SL 20W G4 12V 1CT/24	12 V	20 W	

General Information

Order Code	Full Product Name	Ansi Code	Cap-Base	LIF Code	Life To 50% Failures (Nom)	Operating Position	Philips Code
822234361803	6390 30W G5.3 10.8V 1CT/24	DZA	G5.3	-	1000 h	S90	6390
924041528894	14531 360W G5.3 82V 1CT	EYB	G5.3	-	75 h	S90	14531
923870017103	7023 100W GY6.35 12V 1CT/10X10F	FCR	GY6.35	A1/215	50 h	S90	7023
923872517103	7724 100W GY6.35 12V 1CT/10X10F	EVA	GY6.35	M28	2000 h	S90	7724
923875717103	7724I 100W GY6.35 12V 1CT/10X10F	EVA	GY6.35	-	2000 h	S90	7724I
923870217103	7027 50W G6.35 12V 1CT/10X10F	BRL-BCD	G6.35	A1/220	50 h	S90	7027
923870520503	7158 150W G6.35 24V 1CT/10X10F	FCS	G6.35	A1/216	50 h	S90	7158
923870618503	6550 150W G6.35 15V 1CT/10X10F	EVB-BRJ	G6.35	A1/234	50 h	S90	6550
924006520503	7748XHP 250W G6.35 24V 1CT/10X10F	EHJ	G6.35	A1/223	50 h	S90	7748XHP
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	FCS	G6.35	A1/216	40 h	S90	7158XHP
924049819103	14623 95W G6.35 17V 1CT/10X10F	-	G6.35	-	2000 h	S90	14623
923873910103	6605 10W G4 6V 1CT/10X10F	-	G4	M42	2000 h	UNIVERSAL	6605
923874510103	7387 10W G4 6V 1CT/10X10F	ESA	G4	M29	100 h	S90	7387
923874610103	7388 20W G4 6V 1CT/10X10F	ESB	G4	M30	100 h	UNIVERSAL	7388
923931110103	5761 30W G4 6V 1CT/10X10F	-	G4	-	100 h	UNIVERSAL	5761
924031928303	13701 110W G6.35 22.8V 1CT/10x10F	-	G6.35	-	700 h	S90	13701
924068417104	12345SL 20W G4 12V 1CT/24	-	G4	-	100 h	UNIVERSAL	12345SL

Light Technical

Order Code	Full Product Name	Correlated Color	Color Rendering	Luminous Flux	
		Temperature (Nom)	Index (Nom)	Luminous Flux (Nom)	(Rated) (Nom)
822234361803	6390 30W G5.3 10.8V 1CT/24	3100 K	100	-	570 lm
924041528894	14531 360W G5.3 82V 1CT	3300 K	100	-	10000 lm
923870017103	7023 100W GY6.35 12V 1CT/10X10F	3450 K	100	-	3600 lm
923872517103	7724 100W GY6.35 12V 1CT/10X10F	3300 K	100	-	2800 lm
923875717103	7724I 100W GY6.35 12V 1CT/10X10F	3300 K	100	-	2800 lm

Order Code	Full Product Name	Correlated Color	Color Rendering	Luminous Flux	
		Temperature (Nom)	Index (Nom)	Luminous Flux (Nom)	(Rated) (Nom)
923870217103	7027 50W G6.35 12V 1CT/ 10X10F	3350 K	100	-	1600 lm
923870520503	7158 150W G6.35 24V 1CT/10X10F	3450 K	100	-	5200 lm
923870618503	6550 150W G6.35 15V 1CT/ 10X10F	3450 K	100	-	5600 lm
924006520503	7748XHP 250W G6.35 24V 1CT/ 10X10F	3550 K	100	-	10000 lm
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	3450 K	100	-	6000 lm

Halogen non-reflector

Order Code	Full Product Name	Correlated Color	Color Rendering Index	Luminous Flux	Luminous Flux (Rated)
		Temperature (Nom)	(Nom)	(Nom)	(Nom)
924049819103	14623 95W G6.35 17V 1CT/10X10F	3050 K	-	-	2150 lm
923873910103	6605 10W G4 6V 1CT/10X10F	2700 K	100	150 lm	-
923874510103	7387 10W G4 6V 1CT/10X10F	3200 K	100	200 lm	-
923874610103	7388 20W G4 6V 1CT/10X10F	3350 K	100	460 lm	-

Order Code	Full Product Name	Correlated Color	Color Rendering Index	Luminous Flux	Luminous Flux (Rated)
		Temperature (Nom)	(Nom)	(Nom)	(Nom)
923931110103	5761 30W G4 6V 1CT/10X10F	3200 K	100	765 lm	-
924031928303	13701 110W G6.35 22.8V 1CT/10x10F	3250 K	100	-	3200 lm
924068417104	12345SL 20W G4 12V 1CT/24	3100 K	100	-	640 lm

Mechanical and Housing

Order Code	Full Product Name	Filament Shape
822234361803	6390 30W G5.3 10.8V 1CT/24	Flat
924041528894	14531 360W G5.3 82V 1CT	Flat
923870017103	7023 100W GY6.35 12V 1CT/10X10F	Flat
923872517103	7724 100W GY6.35 12V 1CT/10X10F	Flat
923875717103	7724I 100W GY6.35 12V 1CT/10X10F	Flat
923870217103	7027 50W G6.35 12V 1CT/10X10F	Flat
923870520503	7158 150W G6.35 24V 1CT/10X10F	Flat
923870618503	6550 150W G6.35 15V 1CT/10X10F	Flat
924006520503	7748XHP 250W G6.35 24V 1CT/10X10F	Flat

Order Code	Full Product Name	Filament Shape
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	Flat
924049819103	14623 95W G6.35 17V 1CT/10X10F	Flat
923873910103	6605 10W G4 6V 1CT/10X10F	-
923874510103	7387 10W G4 6V 1CT/10X10F	-
923874610103	7388 20W G4 6V 1CT/10X10F	-
923931110103	5761 30W G4 6V 1CT/10X10F	-
924031928303	13701 110W G6.35 22.8V 1CT/10x10F	Round
924068417104	12345SL 20W G4 12V 1CT/24	-

