



# MSD Platinum (Touring/Stage)

## MSD Platinum 400L Flex UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

### Product data

General Information		Luminous Efficacy (rated) (Nom)	
Operating Position	UNIVERSAL [ Any or Universal (U)]		52 lm/W
Main Application	Stage/Touring	Operating and Electrical	
Life to 50% Failures (Nom)	1500 h	Power (Nom)	470 W
Life to 50% Failures entertainment cycle (Nom)	4000 h	Voltage (Max)	110 V
		Voltage (Min)	85 V
Light Technical		Controls and Dimming	
Color Code	2	Dimmable	Yes
Luminous Flux (Min)	22100 lm	Luminaire Design Requirements	
Luminous Flux (Nom)	24500 lm	Pinch Temperature (Max)	350 °C
Chromaticity Coordinate X (Max)	313	Product Data	
Chromaticity Coordinate X (Min)	280	Full product code	871869965194700
Chromaticity Coordinate X (Nom)	297	Order product name	MSD Platinum 400L Flex UNP/24
Chromaticity Coordinate Y (Max)	316	EAN/UPC - Product	8718699651947
Chromaticity Coordinate Y (Min)	289	Order code	928496405308
Chromaticity Coordinate Y (Nom)	303		
Correlated Color Temperature (Nom)	8000 K		


# MSD Platinum (Touring/Stage)

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	928496405308

Net Weight (Piece)	108.000 g
--------------------	-----------

## Warnings and Safety

## Dimensional drawing



Product	D (max)	O	C (max)
MSD Platinum 400L Flex UNP/24	54 mm	1.2 mm	60 mm

MSD Platinum 400L Flex

## Photometric data

