



MSR Gold™ MiniFastFit (Touring/ Stage)

MSR Gold™ 700 MiniFastFit 1CT/16

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Product data

| General Information | | Color Rendering Index (Nom) | |
|------------------------------------|-----------------------------------|-------------------------------|--------|
| Cap-Base | PGJX28 [PGJX28] | | 65 |
| Operating Position | UNIVERSAL [Any or Universal (U)] | Operating and Electrical | |
| Main Application | Entertainment | Power (Rated) (Nom) | 700 W |
| Life to 50% Failures (Nom) | 750 h | Lamp Current (Nom) | 10.8 A |
| System Description | MiniFastFit | Ignition Supply Voltage (Min) | 220 V |
| Light Technical | | Controls and Dimming | |
| Color Code | - [Not Specified] | Dimmable | Yes |
| Luminous Flux (Min) | 44500 lm | Mechanical and Housing | |
| Luminous Flux (Nom) | 49000 lm | Cap-Base Information | PGJX28 |
| Chromaticity Coordinate X (Nom) | 289 | Luminaire Design Requirements | |
| Chromaticity Coordinate Y (Nom) | 308 | Bulb Temperature (Max) | 950 °C |
| Correlated Color Temperature (Nom) | 6000 K | | |
| Luminous Efficacy (rated) (Nom) | 70 lm/W | | |

MSR Gold™ MiniFastFit (Touring/Stage)


| | |
|-------------------------|----------------------------------|
| Pinch Temperature (Max) | 450 °C |
| Product Data | |
| Full product code | 871829114103700 |
| Order product name | MSR Gold™ 700 MiniFastFit 1CT/16 |
| EAN/UPC - Product | 8718291141037 |
| Order code | 928194105114 |

| | |
|---------------------------------|--------------|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 16 |
| Material Nr. (12NC) | 928194105114 |
| Net Weight (Piece) | 0.053 kg |

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



| Product | D (max) | O (min) | L (min) | L (max) | L | C (max) | F (max) | F (min) | F (min) |
|-------------------------------------------|------------|------------|------------|------------|----------|------------|------------|------------|------------|
| MSR Gold™ 700 MiniFastFit 1CT/16 | 23 mm | 3.5 mm | 55 mm | 57 mm | 56 mm | 116 mm | 36.5 mm | 36 mm | 35.3 mm |

MSR GOLD 700 MiniFastFit

