



Finish : clear

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES 9245 143 44500 0833/000 p.190-1 Of 26/05/2010		HALOGEN LAMP INFRARED INDUSTRIAL STANDARD 13565V 3000W 220 - 250V CL				9245 143 44500 0833/000			26/01/2011						
REF. : PDM N IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ. EUROP 	2 SH	SH 190-1	10	1:1	A4					
NAME : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	3000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2500 K NA	± 100 K
FLUX (HeLeN lamp)	NA	
WEIGHT	80 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 143 44500		26/01/2011					
9245 143 44500		INFRARED INDUSTRIAL STANDARD						0833/000							
0833/000 p. 190-2		13565V 3000W 220-250V CL													
Of 20/10/2003		REF. : PDM IRK 2010-082		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10		A4			
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															