



1	0833	2	0833	3	0000	4	5	6	7	8
SUPERSEDES 9245 449 44900 0833/000 p.190-1 Of 17/06/2004		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14121Z/98 3000W 235V REFL				9245 449 44900 0833/000			05/09/2011	
REF. : IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ. EUROP 	2 SH	SH 190-1	10	1:1	A4
NAME : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe					
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.										

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		3000W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp	2650 K	± 100 K
	Lamp with reflector	2550 K	Indicative value
FLUX (HeLeN lamp)	Clear lamp	NA	
	Reduction	NA	
WEIGHT		40 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 449 44900			05/09/2011				
9245 449 44900		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p. 190-2		14121Z/98 3000W 235V REFL													
Of 17/06/2004		REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															