



Finish : Reflector

1 0833 | 2 0833 | 3 0000 | 4 m : 0 kg | 5 | 6 | 7 | 8

SUPERSEDES 9245 628 49100 0833/000 p.190-1 Of 18/12/2013		HALOGEN LAMP INFRARED INDUSTRIAL 14156C/83 3000W 400V REFL				9245 628 49100 0833/000		05/02/2016	
REF. : CRP 1549	DOCUMENTATION	UNIT mm	PROJ. EUROP 	2 SH	SH 190-1	10	1:2	A4	
NAME : CHARLIER J.P.	VALIDATION : A. PICHARD			DR. FISCHER Europe					
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.									

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	3000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2650 K 2550 K	± 100 K Indicative value
FLUX (HeLeN lamp) Clear lamp Reduction	NA NA	
MAXIMUM IRRADIANCE LEVEL AT 10 CM	15000 W/m ²	Min
WEIGHT	62 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 628 49100			05/02/2016				
9245 628 49100		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		14156C/83 3000W 400V REFL													
Of 03/04/2012		REF. : CRP 1549		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															