



MSD Platinum (Touring/Stage)

MSD Platinum 20 R UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Product data

| General Information | | | | |
|------------------------------------|-----------------------------------|--|--|--|
| Cap-Base | -[-] | | | |
| Operating Position | UNIVERSAL [Any or Universal (U)] | | | |
| Main Application | Stage/Touring | | | |
| Life to 50% Failures (Nom) | 1500 h | | | |
| System Description | Reflector E21.9 TCM | | | |
| | | | | |
| Light Technical | | | | |
| Color Code | 2 | | | |
| Luminous Flux (Nom) | 22400 lm | | | |
| Chromaticity Coordinate X (Max) | 314 | | | |
| Chromaticity Coordinate X (Min) | 280 | | | |
| Chromaticity Coordinate X (Nom) | 296 | | | |
| Chromaticity Coordinate Y (Max) | 316 | | | |
| Chromaticity Coordinate Y (Min) | 290 | | | |
| Chromaticity Coordinate Y (Nom) | 298 | | | |
| Correlated Color Temperature (Nom) | 8000 K | | | |
| Luminous Efficacy (rated) (Nom) | 47 lm/W | | | |
| | | | | |

| Color Rendering Index (Nom) | - |
|-------------------------------|--------|
| | |
| Operating and Electrical | |
| Power (Nom) | 470 W |
| Voltage (Max) | 110 V |
| Voltage (Min) | 85 V |
| | |
| Controls and Dimming | |
| Dimmable | Yes |
| | |
| Mechanical and Housing | |
| Cap-Base Information | - |
| | |
| Luminaire Design Requirements | |
| Bulb Temperature (Max) | 900 ℃ |
| Pinch Temperature (Max) | 350 °C |
| | |

Datasheet, 2018, September 24 data subject to change


MSD Platinum (Touring/Stage)

| Product Data | | | | |
|-------------------------------|--------------------------|--|--|--|
| Full product code | 871829176888300 | | | |
| Order product name | MSD Platinum 20 R UNP/24 | | | |
| EAN/UPC - Product | 8718291768883 | | | |
| Order code | 928197205308 | | | |
| Numerator - Quantity Per Pack | 1 | | | |

| Numerator - Packs per outer box | 24 |
|---------------------------------|--------------|
| Material Nr. (12NC) | 928197205308 |
| Net Weight (Piece) | 136.600 g |


Warnings and Safety


Dimensional drawing



| Product | D (max) | 0 | C (max) |
|--------------------------|---------|--------|---------|
| MSD Platinum 20 R UNP/24 | 58.5 mm | 1.2 mm | 72 mm |

Photometric data







© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.