



MSD Platinum (Touring/Stage)

MSD Platinum 25 R UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Product data


General Information		Operating and Electrical	
Operating Position	UNIVERSAL [Any or Universal (U)]	Power (Nom)	550 W
Main Application	Stage/Touring	Voltage (Max)	115 V
Life to 50% Failures (Nom)	1500 h	Voltage (Min)	85 V
Light Technical		Controls and Dimming	
Color Code	2	Dimmable	Yes
Luminous Flux (Min)	22100 lm	Luminaire Design Requirements	
Luminous Flux (Nom)	24500 lm	Pinch Temperature (Max)	350 °C
Chromaticity Coordinate X (Max)	313	Product Data	
Chromaticity Coordinate X (Min)	280	Full product code	871869961405800
Chromaticity Coordinate X (Nom)	297	Order product name	MSD Platinum 25 R UNP/24
Chromaticity Coordinate Y (Max)	316	EAN/UPC - Product	8718699614058
Chromaticity Coordinate Y (Min)	289	Order code	928495905308
Chromaticity Coordinate Y (Nom)	303	Numerator - Quantity Per Pack	1
Correlated Color Temperature (Nom)	8000 K	Numerator - Packs per outer box	24
Luminous Efficacy (rated) (Nom)	44 lm/W		

MSD Platinum (Touring/Stage)

Material Nr. (12NC)	928495905308
Net Weight (Piece)	108.000 g

Warnings and Safety

Dimensional drawing



MSD Platinum 25 R

Product	D (max)	O	C (max)
MSD Platinum 25 R UNP/24	54 mm	1.4 mm	60 mm

Photometric data

