



Halogen Low Voltage

6423/5H 150W GZ6.35 15V 1CT/10X5F

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.

Product data

General Information		
Cap-Base	GZ6.35 [GZ6.35]	
Philips Code	6423/5H	
ANSI Code	EFR-5H	
LIF Code	A1/223-5H	
Operating Position	UNIVERSAL [Any or Universal (U)]	
Main Application	Disco/Theatre	
Life to 50% Failures (Nom)	500 h	
Light Technical		
Luminous Flux (Rated) (Nom)	720 lm	
Correlated Color Temperature (Nom)	3400 K	
Color Rendering Index (Nom)	100	
Operating and Electrical		
Power (Rated) (Nom)	150 W	
Voltage (Nom)	15 V	

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Material	Quartz-UV Open	
Reflector Finish	Smooth	
Filament Shape	-	
Filament Dimensions WxH	-	
Luminaire Design Requirements		
Bulb Temperature (Max)	900 ℃	
Pinch Temperature (Max)	350 ℃	
Working Distance WD	32 mm	
Product Data		
Full product code	871150040953960	
Order product name	6423/5H 150W GZ6.35 15V 1CT/10X5F	
EAN/UPC - Product	8711500409539	
Order code	924059218504	


Datasheet, 2018, September 5 data subject to change

Halogen Low Voltage

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924059218504

Net Weight (Piece)	0.023 kg

Dimensional drawing



Product	D (max)	C (max)
6423/5H 150W GZ6.35 15V 1CT/10X5F	50 mm	42 mm

