



Halogen non-reflector

7023 100W GY6.35 12V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Product data


General Information			
Cap-Base	GY6.35 [GY6.35]		
Philips Code	7023		
ANSI Code	FCR		
LIF Code	A1/215		
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]		
Main Application	Projection		
Life to 50% Failures (Nom)	50 h		
Light Technical			
Luminous Flux (Rated) (Nom)	3600 lm		
Correlated Color Temperature (Nom)	3450 K		
Color Rendering Index (Nom)	100		
Operating and Electrical			
Power (Rated) (Nom)	100 W		
Voltage (Nom)	12 V		

Mechanical and Housing					
Bulb Material	Quartz-UV Open				
Filament Shape	Flat				
Filament Dimensions WxH	4.2x2.3				
Luminaire Design Requirements					
Bulb Temperature (Max)	900 °C				
Pinch Temperature (Max)	400 °C				
Product Data					
Full product code	871150040981250				
Order product name	7023 100W GY6.35 12V 1CT/10X10F				
EAN/UPC - Product	8711500409812				
Order code	923870017103				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	100				
Material Nr. (12NC)	923870017103				
Net Weight (Piece)	0.003 kg				

Datasheet, 2019, October 8 data subject to change

Halogen non-reflector

Dimensional drawing



7023 100W GY6.35 12V

Product	D (max)	L (min)	L (max)	L	P (max)	Р	P (min)	C (max)
7023 100W	11.5 mm	29.75	30.25	30	1.30 mm	1.25	1.20	44 mm
GY6.35 12V		mm	mm	mm		mm	mm	
1CT/10X10F								

